

AMITTARI INSTRUMENTS

Window Tint Meter AT-170

Product Description

The Window Tint Meter is applicable to measure the transmittance of all kinds of transparent, translucent samples with parallel plane (such as automobile manufacturing, aerospace, glass products, plastic sheet, sheet, etc). Also can be used to determine the turbidity or clarity of liquid sample (water, drinks and so on).

Product Feature

- This Meter is a hand held device that measures the amount of light that passes through a window.
- Technology is designed in accordance with GB 2410-80, ASTM D1033-61, JIS k7105-81 and other standards.
- Digital display, wide range, high resolution.
- One key calibration, easy to use.
- Solid structure, small volume, light weight, easy to carry.
- Use USB data output to connect with PC.
- Provide Bluetooth data output choice.



by Amittari design

Product Parameter

Display	LCD
Range	0~100%
Resolution	0.1
Accuracy	±2%
Sample Thickness	≤ 10mm / 0.4inch
Light Source	LED
Temp.	0~50°C
Humidity	< 90%
Power Supply	4x1.5V AAA (UM-4) Battery
Size	184x70x30mm
Weight	160g (Not Including Batteries)

Product Accessories

Standard Accessories	Main Unit
	Testing Block
	Carrying Case (B04)
	Operation Manual
Optional Accessories	USB Data Cable with Software
	Bluetooth Data Adapter with Software