AMILIARIINSTRUMENTS

Surface hardness tester for casting/wet mold sand

FEATURES

- * The Sand Mould Surface Hardness Tester is used to measure the surface hardness of the sand mould/core of the wet mold and provide technical parameters for the formulation of the molding process.
- * The surface hardness of sand mold is divided into three types: A, B and C, The common model is type B, among them: Type A: Suitable for the surface hardness test of fine sand mold/core in manual or mechanical low and medium pressure molding.

Type B: Suitable for the surface hardness test of fine and coarse sand mold/corein manual or mechanical low and medium pressure molding.

Type C: Suitable for the surface hardness test of sand mold in high pressuremolding.

- * The unit of type B hardness tester for sand mold surface is (g/mm²), but it is customary to use hardness H(A/B/C) I nstead of unit. Because their values are elated and consistent, the corresponding hardness value is also large when the unit value is large (g/mm²).
- * Low voltage indicator.
- * Digital display gives exact reading with no guessing or errors.
- * Can communicate with PC for recording, printing and analysing by the optional software and cable for RS232C interface.
- * Automatic power off to conserve power.

technical specifications

| model | AS-120S-A | AS-120S-B | AS-120S-C |
|------------------------------|--|-------------|------------|
| compression travel | 2.50mm | 2.50mm | 2.50mm |
| load | 237g | 980g | 1500g |
| To load | 90g | 50g | 180g |
| Shape and size of indenter | BALL:R2.50 | BALL:R12.70 | BALL:R1.20 |
| measurement unit | HA | НВ | HC |
| display parameter | Hardness value/average value/maximum value | | |
| display | 4-bit 10mm liquid crystal | | |
| indication range | 0~100 HA(HB/HC) | | |
| measuring range | 10~90 HA(HB/HC) | | |
| Accuracy | ≤±1 HA(HB/HC) | | |
| resolution ratio | 0.1 HA(HB/HC) | | |
| Low Voltage Warning | √ | | |
| Automatic shutdown function | V | | |
| work environment | temperature: 0~40°Chumidity: <80%RH | | |
| power supply | 2x1.5v AA | | |
| size | 170x65x27mm | | |
| Weight (excluding batteries) | 170g | | |



model selection

| lo | W | | | mediun | 1 | | high | |
|----|------------------------------|-------|---------|--------|-----|-----|------|--|
| | Туре | A (fo | or fine | sand) | | | | |
| | Type B(for fine/coarse sand) | | | | | | | |
| | | | | | Тур | e C | | |
| | | | | | | | | |

Accessories

| Accessories | host | |
|----------------------|--------------------------------|--|
| | Portable Case (B04) | |
| | operating manual | |
| Optional accessories | USB online cable and software | |
| | Bluetooth adapter and software | |

